

**IN THE CLAIMS**

Please amend the claims as indicated below:

1. (Previously Presented) An apparatus for processing a received signal containing a datastream containing data packets, comprising:
  - a signal decoder, the signal decoder generating a first error signal in response to indecipherable data received by the decoder; and
  - a transport processor, the transport processor receiving the first error signal, the transport processor generating a second error signal after receiving the first error signal wherein the second error signal begins at an earlier time than an associated data packet, and
  - wherein the second error signal ends at a later time than the associated data packet.
2. (Original) The apparatus of claim 1, wherein the datastream comprises a modulated signal containing data packets.
3. (Previously Presented) The apparatus of claim 2, further comprising:
  - a transport bus, the transport bus forwarding data packets to subsequent processing stages; and
  - at least one synchronization signal, the transport processor generating the second error signal in response to receiving the synchronization signal.
4. (Previously Presented) The apparatus of claim 3, wherein the second error signal is forwarded to the transport bus so as to have a synchronized relationship to the data packets being forwarded via the transport bus.
5. (Previously Presented) The apparatus of claim 5, wherein the second error signal is formed as a series of logical high frames, each logical high frame being associated with a data packet.
6. (Cancelled)

7. (Cancelled)
8. (Cancelled)
9. (Previously Presented) The apparatus of claim 3, further comprising a demodulator, the demodulator deriving the synchronization signal from the received signal.
10. (Previously Presented) The apparatus of claim 1 wherein the transport processor is implemented as a microprocessor.
11. (Previously Presented) A system for generating an error signal based on an error encountered while processing a received signal which includes an image representative datastream containing data packets, comprising:
  - a forward error detecting and correcting decoder which generates a first error signal;
  - a synchronization signal derived from the received signal;
  - a transport processor interconnected to receive the first error signal and the synchronization signal, the transport processor generating a second error signal in response to the first error signal and the synchronization signal, wherein the second error signal begins at an earlier time than an associated data packet, andwherein the second error signal ends at a later time than the associated data packet.
12. (Previously Presented) The system of claim 11, further comprising a transport bus, the data packets being forwarded to subsequent processing stages via the transport bus.
13. (Previously Presented) The system of claim 12, wherein the second error signal is forwarded via the transport bus simultaneously with the data packets associated with the second error signal.
14. (Previously Presented) The system of claim 13, wherein the data packets are forwarded as a series of discrete spaced apart frames, the second error signal being adapted to

indicate an error in a defective data packet by having a duration that spans the frame of the defective data packet.

15. (Previously Presented) The system of claim 14, wherein the second error signal assumes a logical low state when no error is present in a data packet.

16. (Previously Presented) The system of claim 15, wherein the forward error detecting and correcting decoder is a Reed-Solomon decoder.

17. (Previously Presented) The system of claim 11 wherein the transport processor is implemented as a microprocessor.

18. (Currently Amended) A method for processing a received signal containing an image representative datastream containing data packets received by a digital television receiver, a packet error signal generating method, comprising the steps of:  
demodulating the received signal to produce a demodulated signal;  
error detecting the demodulated signal to produce a first error signal;  
forwarding the first error signal to a transport processor;  
forwarding a synchronization signal to the transport processor, thereby associating the first error signal with a particular data packet; and  
generating a second error signal in response to the synchronization signal being received by the transport processor, the second error signal beginning at an earlier time and ending at a later time than the particular data packet.

19. (Previously Presented) A method according to claim 18, further comprising the step of generating the second error signal as a series of discrete frames, each frame having a duration greater than an associated data packet.

20. (Cancelled)

21. (Original) A method according to claim 19, wherein the error detecting step comprises Reed-Solomon error detection and correction.

22. (Previously Presented) An apparatus for processing a received signal containing a datastream, comprising:

a signal decoder, the signal decoder generating a first error signal in response to indecipherable data received by the decoder; and

a transport processor generating a second error signal after receiving the first error signal,

wherein the second error signal is formed as a series of logical high frames, each logical high frame being associated with a data packet,

wherein each logical high frame of the second error signal begins at an earlier time than the data packet associated with the logical high frame, and

wherein each logical high frame of the second error signal ends at a later time than the data packet associated with the logical high frame.